



Fuse-link, high speed, 1400 A, AC 850 V, size 3, 76 x 76 x 76 mm, aR, IEC, single indicator

Part no. **FUSE 1400A 850V 3BN/75 AR**
 Catalog No. **170M6032**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1400
Rated voltage			AC 850 V
Construction size			size 3
Size			76 x 76 x 76 mm
Utilization category			aR
Status indicator			single indicator
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			3
Type of current			AC
Rated voltage AC		V	850
Rated voltage DC		V	
Rated current		A	1400
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			Top fuse status indicator
Power loss at rated current		W	
Mounting holes			Other
Centre-to-centre distance of connections		mm	75.4